

**MATERIAL SAFETY DATA SHEET****SPAL-PRO 2000 "A"**

---

**1. PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT NAME: Spal-Pro 2000 "A"

PRODUCT DESCRIPTION: Polyol part of a two-component poured polyurethane elastomer

MANUFACTURED BY

Metzger McGuire Co., Inc.

557 Route 3-A

Bow, NH 03304

800-223-6680 www.metzgermcguire.com

24 HOUR EMERGENCY TELEPHONE NUMBER

Chemtrec: 800-424-9300

---

**2. COMPOSITION / INFORMATION ON INGREDIENTS**

<u>Chemical Name</u>	<u>Wt.%</u>	<u>CAS</u>
6-Methyl-2,4-Bis(Methylthio)Phenylene-1,3-Diamine	10-15	106264-79-3
N,N,N',N'-Tetrakis(2-Hydroxypropyl)Ethylenediamine	<= 10	102-60-3
Polyether Polyol	75-85	9082-00-2

---

**3. HAZARDS IDENTIFICATION****EMERGENCY OVERVIEW**

PHYSICAL APPEARANCE: Various colors, including but not limited to: Gray, Black, Brown, Cream.

IMMEDIATE CONCERNS: Irritating to eyes, skin, gastrointestinal tract, and respiratory system.

**POTENTIAL HEALTH EFFECTS**

EYES: May cause moderate irritation.

SKIN: May cause mild to moderate irritation.

INGESTION: Ingestion may cause irritation of the gastrointestinal tract and gastrointestinal discomfort with any or all of the following symptoms: nausea, vomiting, lethargy, or diarrhea.

INHALATION: Inhalation of vapors or mist at concentrations above the TLV can cause respiratory tract irritation. (nose, throat, lungs)

**SIGNS AND SYMPTOMS OF OVEREXPOSURE**

EYES: Contact may cause moderate irritation consisting of transient redness, swelling, and mucous membrane discharge to the conjunctiva.

SKIN: Contact may cause mild irritation consisting of transient redness and/or swelling.

INGESTION: Ingestion may cause gastrointestinal discomfort.

INHALATION: High concentrations may be irritating to in nose, throat, and lungs.

ROUTES OF ENTRY: Inhalation, skin contact, eye contact, ingestion.

---

#### 4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get immediate medical attention.

SKIN: Remove contaminated clothing. Wash affected areas thoroughly with soap and water. Wash clothing thoroughly before reuse. Discard shoes. Get medical attention if swelling or redness occurs, or if irritation persists after being washed.

INGESTION: Do not induce vomiting. Never give anything by mouth to a drowsy or unconscious person. If the individual is conscious, rinse mouth with water. Give 1 to 2 cups of water to drink. Seek immediate medical attention.

INHALATION: Remove individual from exposure, keep warm and at rest. If respiratory irritation develops, get medical attention.

---

#### 5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: > 300 °F (Closed Cup)

EXTINGUISHING MEDIA: Dry Chemical, Carbon Dioxide, Alcohol Foam, Water Fog or Spray. Water or foam may cause frothing if liquid is burning, but it still may be a useful extinguishing agent if carefully applied to the fire.

HAZARDOUS COMBUSTION PRODUCTS: Carbon Monoxide, Carbon Dioxide

FIRE FIGHTING PROCEDURES: Isolate fuel supply from fire. Use water spray to cool fire-exposed surfaces and containers. Avoid spreading burning liquid with water used for cooling purposes. Fire fighters should wear self-contained breathing apparatus in addition to emergency fire fighting protective clothing.

---

#### 6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Clean up spills wearing proper personal protective equipment. (See section 8) Absorb with dry chemical absorbent, earth, sand, or any other inert material. Place in a chemical waste container.

LARGE SPILL: Create a dike or trench to contain materials. Prevent entry into waterways, sewers, basements or confined areas. Clean-up personnel should wear appropriate personal protection equipment. (see section 8) May be a slipping hazard. Absorb with dry chemical absorbent, earth, sand, or any other inert material. Place in a chemical waste container. Wash residues from area with soap and water and rinse. Contaminated water should be retained and not allowed to flow into ground or surface water.

**ENVIRONMENTAL PRECAUTIONS:** This product is a marine pollutant.

**SPECIAL PROTECTIVE EQUIPMENT:** See Section 8. Clean-up crews should always wear Personal Protective Equipment.

**COMMENT:** Dispose of by any standard method of disposal in accordance with good industrial practice and in compliance with federal, state, and local environmental protection regulations.

## 7. HANDLING AND STORAGE

**HANDLING:** Wear proper personal protective equipment. Use in a well ventilated area. Avoid smoking, bare lights, or ignition sources. Avoid physical damage to containers. Practice good hygiene procedures.

**STORAGE:** Protect from atmospheric moisture. Keep containers sealed in order to avoid contamination. Do not reseal if contaminated. Store indoors in a cool, well-ventilated area.

**STORAGE TEMPERATURE:** 60 °F – 120 °F

**SHELF LIFE:** 6 months

**SPECIAL SENSITIVITY:** Material is hygroscopic and may absorb small amounts of atmospheric moisture.

**COMMENT:** See Section 10 for more information on precautions concerning storage and handling of this material.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**EXPOSURE GUIDELINES:**

OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200)

<u>CHEMICAL NAME</u>		<u>EXPOSURE LIMITS</u>					
		<u>OSHA PEL</u>		<u>ACGIH TLV</u>		<u>SUPPLIER OEL</u>	
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
6-Methyl-2,4-Bis(Methylthio)Phenylene-1,3-Diamine	<b>TWA</b>	NE	NE	NE	NE		
N,N,N',N'-Tetrakis(2-Hydroxypropyl)Ethylenediamine	<b>TWA</b>	NL	NL	NL	NL		

**KEY:**

NE = Not Established

NL – Not Listed

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels.

**PERSONAL PROTECTIVE EQUIPMENT**

**EYES AND FACE:** Wear safety glasses with side shields.

**SKIN:** Wear impervious gloves and clothing to cover exposed skin.

**RESPIRATORY:** If adequate engineering controls are not feasible, an approved respirator must be worn.

**WORK HYGIENIC PRACTICES:** Follow good normal hygiene practices. Avoid contact with skin. Avoid eating, drinking, or smoking while using this product. Wash hands thoroughly after use.

**OTHER PROTECTIVE EQUIPMENT:** Safety showers and eye wash stations are recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**PHYSICAL STATE:** Liquid

**ODOR:** Slightly musty

**COLOR:** Various colors, including but not limited to: Gray, Black, Brown, Cream

**BOILING POINT:** > 300 °F

**FREEZING POINT:** < 32 °F

**SOLUBILITY IN WATER:** Partially soluble

**SPECIFIC GRAVITY:** 1.040 – 1.080 (water = 1) at 74 °F

**VISCOSITY:** 1350 – 1550 Centipoise at 74 °F

## 10. STABILITY AND REACTIVITY

**CONDITIONS TO AVOID:** Temperature extremes. Container contamination. Moisture.

**STABILITY:** Stable under recommended storage conditions.

**POLYMERIZATION:** Will not occur.

**HAZARDOUS DECOMPOSITION PRODUCTS:** By fire: Carbon Monoxide, Carbon Dioxide, Oxides or Nitrogen, Oxides of Sulfur.

**INCOMPATIBLE MATERIALS:** Moisture, strong oxidizing agents, temperature extremes.

## 11. TOXICOLOGICAL INFORMATION

	ORAL LD <sub>50</sub> (rat)	DERMAL LD <sub>50</sub> (rabbit)	INHALATION LC <sub>50</sub> (rat)
6-Methyl-2,4-Bis(Methylthio)Phenylene-1,3-Diamine	> 1515 mg/kg	> 2000 mg/kg	
N,N,N',N'-Tetrakis(2-Hydroxypropyl)Ethylenediamine	3280 mg/kg	> 2000 mg/kg	

**EYE EFFECTS:** Moderate irritant

**SKIN EFFECTS:** Mild to moderate irritant

**CARCINOGENICITY**

IARC: Not classified as a carcinogen.  
NTP: Not classified as a carcinogen.  
OSHA: Not classified as a carcinogen.  
ACGIH: Not classified as a carcinogen.

---

## 12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATE: This product is a marine pollutant.

COMMENTS: No testing for product as a whole.

---

## 13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Disposal should be in accordance with local, state, provincial or national regulations.

EMPTY CONTAINER: Empty containers should be decontaminated and either passed to an approved drum recycler or destroyed.

RCRA HAZARD CLASS: This material is not a hazardous waste under RCRA 40 CFR 261.

COMMENTS: The generation of waste should be avoided or minimized whenever possible. Chemical waste, even small quantities, should never be poured down drains, sewers or waterways. Refer to Section 6 for additional information.

---

## 14. TRANSPORT INFORMATION

TECHNICAL NAME: Compound Resin

### DOT (DEPARTMENT OF TRANSPORTATION)

Bulk containers (>119 gallon capacity) are regulated as: UN3082, Environmentally Hazardous Substances, Liquid, N.O.S. (Aromatic amines), 9, III. Non-bulk containers are not regulated unless any part of shipment will be by vessel.

### VESSEL (IMO/IMDG)

All containers are regulated as: UN3082, Environmentally Hazardous Substances, Liquid, N.O.S. (Aromatic amines), 9, III. When shipping non-bulk packages and a hazardous material meets the definition of a marine pollutant, it must be identified as a marine pollutant if any portion of transportation is by vessel.

---

## 15. REGULATORY INFORMATION

### UNITED STATES

#### SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Immediate, Delayed

313 REPORTABLE INGREDIENTS: This product does not contain any chemical components with known CAS numbers that exceed their *de minimis* reporting levels.

**CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)**

No chemicals in this material with known CAS numbers are subject to the reporting requirements of CERCLA.

**TSCA (TOXIC SUBSTANCE CONTROL ACT)**

TSCA REGULATORY: All ingredients are on TSCA inventory.

RCRA STATUS: Not hazardous if discarded in its purchased form. However, under RCRA, it is the responsibility of the product user to determine at the time of disposal whether a material containing the product or derived from the product should be classified as a hazardous waste (40 CFR 261.20-24).

OSHA HAZARD COMM. RULE: This material is classified as a hazardous material under the criteria outlined in the OSHA Hazard Communication Standard (HCS) at 29 CFR 1910.1200.

---

**16. OTHER INFORMATION**

HMIS RATING: Health – 2\*, Flammability - 1, Physical Hazard - 0

HMIS RATING NOTES: If present, the asterisk signifies a chronic health hazard.

Rating system: 0 = low hazard to 4 = high hazard

MANUFACTURER, SUPPLIER, OR DISTRIBUTOR DISCLAIMER: The information in this MSDS was obtained from sources that we believe are reliable. The information is provided without warranty, implied or expressed, concerning accuracy. The manufacturer or supplier assumes no legal responsibility for use or reliance on this information. This MSDS is provided solely for the purpose of conveying health, safety, and environmental information. This MSDS is not a specification data sheet. Some of the information and conclusions may be derived from sources other than test data on the material itself.

**KEY LEGEND INFORMATION:**

ACGIH - American Conference of Governmental Industrial Hygienists

EPA - Environmental Protection Agency

IARC - International Agency for Research on Cancer

NTP - National Toxicology Program

OEL - Occupational Exposure Limit

OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit

STEL - Short Term Exposure Limit

TLV - Threshold Limit Value

TWA - Time Weighted Average

PREPARED BY: L. Priest

DATE ISSUED: 2/11/2005

MSDS #: SPAL-PRO 2000 A

REVISION # and DATE: Rev #6, 9/30/2008

CHANGES FROM LAST VERSION: Section 14 [Transportation Information]